

NEW
VERSION

LEDZILLA²[®]

dedolight[®]

LED ON BOARD-LIGHT

THE DEDOLIGHT[®] MINI-DLOB



DLOBML2 Ledzilla2 – On Board - Light

This light head works with a single, high-power LED

- Amazing output in combination with dedolight double aspheric optics.
- Focuses like a dedolight. LED lights are usually not focusable.
- No other focusing LED light compares - 4° to 56°.
- Power consumption is only 8W despite its high output.
- Operates from -40°C up to +40°C.
- LED power available indicator.
- Front-end bayonet mount allows the addition of attachments and light modifiers.

PHOTOMETRICS: DLOBML2

Distance	Meter	1	2	3	4	5	10
	Feet	3'	6'	9'	12'	15'	30'
Flood	Lux	435	109	48			
	Foot Candle	40	10	4,5			
Medium	Lux	957	239	106	60		
	Foot Candle	89	22	9,9	5,6		
Spot	Lux	5400	1350	600	338	216	54
	Foot Candle	502	126	56	31	20	5

NEW:

A bicolor version of the Ledzilla will be introduced shortly. Tuneable color from 2700 - 6000 Kelvin.

The Ledzilla Bicolor will accept a rotating 8 leaf barn door (same as featured by the DLED2.1 light heads).

All other Ledzilla accessories are also compatible.

- Smooth light distribution in all and every focusing position.
- Wide-angle flip-up diffuser for 70° angle, smoothly covers wide-angle zooms.
- Clean, sharp, single edge barn door shadow OR a very gentle light and shadow transition with the flip-up diffuser in place
- Converts from daylight to tungsten via flip-down filter
- Color rendition and color distribution is cleaner than comparable LED lights.
- Powers from any 6V to 18V DC power source.
- Optional battery shoes are compatible with Sony, Panasonic, Canon and Nikon mini-DV batteries.
- NP-F550 7.2V, 2000 mA, 105 minute run time.
- NP-F750 7.2V, 4000 mA, 210 minute run time.
- NP-F950 7.2V, 6000 mA, 330 minute run time.

When dimmed to 50% light output, power consumption drops accordingly resulting in twice the run time. Alternative power from any Anton/Bauer or PAG system, car cigarette lighter output or battery belt.

Options:

Soft-Tube, Softbox, White Dome

Attach by front end bayonet mount



DLOBML-LT20

Soft tube, 8"/20 cm long – Ideal for soft light in confined areas, e.g., car interior at night. Detachable light shaper – folding plastic barn doors.



DLOBML-SBX12

Soft box, 5"/12 cm wide – Gentle fill light, easy to look at, ideal for close ups. Filter slot accepts tungsten conversion filter.

DLOBML-SBX12-CTO

Interchangeable front diffuser with color conversion to 3200K (not shown)



DLOBML-WD15

White dome (china lantern) soft box, 5.9"/15 x 15 cm gentle light, evenly distributed, perfect as general fill light. Side covers can be opened individually.

DLOBML-TCF

Tungsten conversion filter for filter slot of all three accessories. Same filter slot serves for gel strips from any common swatch book. Allows nearly any kind of color effect.